

P985 TH

Extremely compact design for this Thermo pellet stove of just 32 cm. Cladded with a large-sized front panel of Majolica: Bianco, Ardesia, Canapa, Grigio Cerato, Rosso Lava and Terra Oriente. Top part in Majolica including the Rolling top system for easy topping up with pellets. Perfect for being installed in corridors.



GENERAL FEATURES

- Heating: hot water production
- Cladding: majolica
- Rolling Top: sliding top
- Top: majolica
- One-piece firebox: steel
- Boiler: steel
- Firebox: steel - Aluker®
- Fume deflector: steel
- Ash conveyor: steel
- Exchanger cleaning: rotor cleaning system, Patented
- Brazier: cast iron
- Expansion tank: as standard feature
- Standard circulator pump: high efficiency
- Safety valve and relief valve: as standard feature
- Door: steel - cast iron with ceramic glass resistant to 750°C
- Handle: steel with nickel-plated finish
- Standard flue outlet position: RH rear - RH side - RH top
- Remote control with LCD display: yes
- Function control: control panel with digital controls
- Power adjustment: automatic with 16 levels depending on the set temperature
- Timer-controlled thermostat with programming: 6 daily time frames
- Ceramic glass: resistant to 750°C
- Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Energy Saving: yes
- Eco Function: yes
- Frost Function: yes
- Probe for managing storage tank: as standard feature
- Probe for managing DHW storage tank: as standard feature
- Can be connected to an external thermostat: yes
- AUX control: yes
- Ash vacuum cleaner: as standard feature
- Electronically-controlled anti-condensation valve: optional
- Installation: wall - flush with the corner
- Flush with the wall installation: yes
- Combustion air kit: optional

TECHNICAL DETAILS

- Energy efficiency class A+
- Rated thermal power (min - max) kW 5,6 - 13,2
- Efficiency (min - max) % 91,4 - 92,5
- Max operating pressure bar 1.5
- 3-bar safety discharge valve Ø 1/2"
- Heat system delivery Ø 3/4"
- Heat system return Ø 3/4"
- Rated consumption (min - max) kg/h 1,2 - 2,9
- Weight kg 215
- Standard flue outlet Ø cm 8
- Model P985 TH

COVERS

