

IL wood-burning insert, specially designed to be installed in existing traditional fireplaces, improving their performance and safety and making them easier to use. Also ideal for first installations.

IL 65/56 V



GENERAL FEATURES

- Heating: natural convection and radiation, forced convection ventilation as standard feature or optional according to the model, forced ventilation with Multifuoco System® or Multifuoco System Plus optional according to the model
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: cast iron
- Opening: door in steel with self-cleaning ceramic glass resistant to 750°C. Openable with
- Handle: concealed detachable handle in steel (mod. IL)
- Primary air: manually adjustable
- Tertiary air: pre-determined and pre-heated
- Flue gas adjustment: automatic and adjustable
- Standard flue outlet position: top
- Fuel: wood

TECHNICAL DETAILS

- Energy efficiency class A
- Rated output max kW 7,0
- Rated efficiency power % 80
- Rated consumption max kg/h 1.9
- Firebox opening (W) - Dimensions for the passage of wood cm 49
- Firebox opening (H) - Dimensions for the passage of wood cm 24,5
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 65
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 56
- Weight kg 120
- Model IL 65/56 V

