MA 263 B SL PLUS

GENERAL FEATURES

•Heating: natural convection, radiation or optional ductable forced ventilation with the Multifuoco System® or Multifuoco System Plus,

*Structure: coated steel with closed firebox

•Firebox: Aluker®

·Hearth: cast iron

·Hood: steel

•Door profile: coated steel

·Handle: in painted steel, removable

•Primary air: manually adjustable

Secondary air: pre-determined

•Flue gas adjustment: with manually adjustable valve

•Standard flue outlet position: top

•Fuel: wood

The MA 263 B SL by Piazzetta is the One-piece Firebox with Vertically-sliding Door and Natural Convection for Wood Fireboxes that will ensure you low consumption, high efficiency and easy installation. Find out further information

TECHNICAL DETAILS

- •Energy efficiency class A+ •Rated output max kW 13,5
- •Rated efficiency power % 80,8
- •Rated consumption max kg/h 4,0
- Vertically sliding opening cm 30
- •Firebox opening (W) Dimensions for the passage of wood cm 87,5
- •Firebox opening (H) Dimensions for the passage of wood cm 22,5
- •Mouth of firebox (W) Minimum dimensions of mouth of cladding cm 90,5
- •Mouth of firebox (H) Minimum dimensions of mouth of cladding cm 45
- •Weight kg 235 •Model MA 263 B SL PLUS



