## MA 271 SL PLUS



## **GENERAL FEATURES**

- Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus single or double, ducting
- •Structure: coated steel with closed firebox
- ·Firebox: Aluker®
- •Hearth: cast iron
- ·Hood: steel
- Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. With vertically-sliding opening and door for cleaning
- Door profile: coated steel
- ·Handle: coated steel
- •Primary air: manually adjustable
- Secondary air: pre-determined
- •Flue gas adjustment: with manually adjustable valve
- Standard flue outlet position: top
- •Fuel: wood

## **TECHNICAL DETAILS**

- Energy efficiency class A
- •Rated output max kW 16,0
- •Rated efficiency power % 77,5
- •Rated consumption max kg/h 5,2
- Vertically sliding opening cm 35
- •Firebox opening (W) Dimensions for the passage of wood cm 84,5
- \*Firebox opening (H) Dimensions for the passage of wood cm 27.5
- \*Mouth of firebox (W) Minimum dimensions of mouth of cladding cm 98
- \*Mouth of firebox (D) Minimum dimensions of mouth of cladding cm 53
- \*Mouth of firebox (H) Minimum dimensions of mouth of cladding cm 51,5  $\,$
- Weight kg 302
- •Model MA 271 SL PLUS



