## **MA 285 D/S SL**



## **GENERAL FEATURES**

- ·Heating: natural convection and radiation
- ·Structure: coated steel with closed firebox
- ·Firebox: Aluker®
- ·Hearth: cast iron
- •Hood: steel
- \*Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. Openable with vertically-sliding system and door for cleaning
- •Door profile: coated steel
- ·Handle: coated steel
- •Primary air: manually adjustable
- Secondary air: pre-determined
- •Flue gas adjustment: with manually adjustable valve
- ·Standard flue outlet position: top
- ·Fuel: wood

## **TECHNICAL DETAILS**

- ·Energy efficiency class A
- •Rated output max kW 12,5
- •Rated efficiency power % 72.5
- •Rated consumption max kg/h 4.1

- Vertically sliding opening cm 37
  Firebox opening (W) Dimensions for the passage of wood cm 66
  Firebox opening (H) Dimensions for the passage of wood cm 32,5
- •Mouth of firebox (W) Minimum dimensions of mouth of cladding cm 75,5
- •Mouth of firebox (D) Minimum dimensions of mouth of cladding cm 43
- ·Mouth of firebox (H) Minimum dimensions of mouth of cladding cm 51
- •Weight kg 185
- •Model MA 285 DX SL



