

Wood firebox that blends clean design lines with ease of use. Its perfect construction linearity offers a wide variety of installation options. The screen-printed glass frames the fire and makes it the distinctive feature of the home.

# MC 65/60 SL



## GENERAL FEATURES

- Heating: natural convection, radiation or optional ductable forced ventilation with the Multifuoco System® or Multifuoco System Plus,
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: Aluker®
- Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. With vertically-sliding opening and door for cleaning
- Door profile: coated steel
- Handle: removable
- Primary air: manually adjustable
- Secondary air: manually adjustable
- Tertiary air: pre-determined and pre-heated
- Standard flue outlet position: top
- Fuel: wood

## TECHNICAL DETAILS

- Energy efficiency class A
- Rated output max kW 11,0
- Rated efficiency power % 80
- Rated consumption max kg/h 3.1
- Vertically sliding opening cm 49
- Firebox opening (W) - Dimensions for the passage of wood cm 54,5
- Firebox opening (H) - Dimensions for the passage of wood cm 41
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 65,5
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 60,5
- Weight kg 202
- Model MC 65/60 SL

