

Piazzetta's ME 90 D/S is a wood-burning fireboxes with an innovative and calibrated rise and fall door. Available in natural convection or with the forced air, single or dual fan Multifuoco® System or Multifuoco System Plus.

# ME 90 D/S



## GENERAL FEATURES

- Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus single or double, ducting
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: cast iron
- Hood: steel
- Opening: door in enamelled steel with self-cleaning ceramic glass resistant up to 750 C°. Rise n'fall door for wood loading, hinged opening for cleaning
- Door profile: for flush dry wall installation, in painted steel 12 cm depth
- Handle: in painted steel, removable
- Primary air: manually adjustable
- Secondary air: pre-determined
- Flue gas adjustment: manual valve opening with console on firebox
- Standard flue outlet position: top
- Fuel: wood
- Combustion air kit: optional

## TECHNICAL DETAILS

- Energy efficiency class A+
- Rated output max kW 16,0
- Rated efficiency power % 81,0
- Rated consumption max kg/h 4,8
- Vertically sliding opening cm 32
- Firebox opening (W) - Dimensions for the passage of wood cm 78,5
- Firebox opening (H) - Dimensions for the passage of wood cm 24,5
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 100
- Mouth of firebox (D) - Minimum dimensions of mouth of cladding cm 61
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 51
- Weight kg 330
- Model ME 90 D

