

# P988 TH

Thermo Pellet stove, fully clad in Majolica in the following colours: Bianco, Ardesia, Canapa, Grigio Cerato, Rosso Lava and Terra Oriente. In addition to heating the water in the heating system, it also heats the room via radiation, enhancing all the pleasure of fire to the full. It is fitted with cutting-edge technology as a standard feature, ensuring top performance at all times.



## GENERAL FEATURES

- Heating: hot water production
- Cladding: majolica
- Top: majolica and steel
- One-piece firebox: steel
- Boiler: steel
- Firebox: steel - Aluker®
- Fume deflector: Skamolex
- Ash conveyor: steel
- Exchanger cleaning: rotor cleaning system, Patented
- Brazier: cast iron
- Expansion tank: as standard feature
- Standard circulator pump: high efficiency
- Safety valve and relief valve: as standard feature
- Door: steel - cast iron with ceramic glass resistant to 750°C
- Handle: steel with nickel-plated finish
- Optional flue outlet: LH side
- Standard flue outlet position: LH rear
- Remote control with LCD display: yes
- Function control: control panel with digital controls
- Power adjustment: automatic with 16 levels depending on the set temperature
- Timer-controlled thermostat with programming: 6 daily time frames
- Ceramic glass: resistant to 750°C
- Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Energy Saving: yes
- Eco Function: yes
- Frost Function: yes
- Probe for managing storage tank: as standard feature
- Probe for managing DHW storage tank: as standard feature
- Can be connected to an external thermostat: yes
- AUX control: yes
- Ash vacuum cleaner: as standard feature
- Flue gas chamber ash pan: removable
- Electronically-controlled anti-condensation valve: optional
- Installation: flush with the wall / corner
- Flush with the wall installation: yes
- Combustion air kit: optional

## TECHNICAL DETAILS

- Energy efficiency class A+
- Rated thermal power (min - max) kW 5,8 - 20,7
- Efficiency (min - max) % 90,0 - 91,5
- Max operating pressure bar 1.5
- 3-bar safety discharge valve Ø 1/2"
- Heat system delivery Ø 3/4"
- Heat system return Ø 3/4"
- Rated consumption (min - max) kg/h 1,3 - 4,6
- Weight kg 232
- Standard flue outlet Ø cm 10
- Model P988 TH

## COVERS

