

The MA 261 SL PLUS by Piazzetta is the One-piece Firebox with Vertically-sliding Door and Natural Convection for Wood Fireboxes that will ensure you low consumption, high efficiency and easy installation. Find out further information.

MA 261 SL PLUS

GENERAL FEATURES

- Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus single or double, ducting
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: cast iron
- Hood: steel
- Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. Openable with vertically-sliding system and door for cleaning
- Door profile: coated steel
- Handle: coated steel
- Primary air: manually adjustable
- Secondary air: pre-determined
- Flue gas adjustment: with manually adjustable valve
- Standard flue outlet position: top
- Fuel: wood

TECHNICAL DETAILS

- Energy efficiency class A+
- Rated output max kW 14,0
- Rated efficiency power % 85,2
- Rated consumption max kg/h 4,0
- Vertically sliding opening cm 37,5
- Firebox opening (W) - Dimensions for the passage of wood cm 76,0
- Firebox opening (H) - Dimensions for the passage of wood cm 30
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 79,5
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 55,5
- Weight kg 258
- Model MA 261 SL PLUS