## **MA 263 SL PLUS**

**GENERAL FEATURES** 

•Heating: natural convection, radiant and forced ventilation kit optional through Multifuoco System® or Multifuoco System Plus single or double, ducting

\*Structure: coated steel with closed firebox

•Firebox: Aluker® ·Hearth: cast iron

·Hood: steel

•Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. Openable with vertically-sliding system and door for cleaning

•Door profile: coated steel

·Handle: coated steel

Primary air: manually adjustable
Secondary air: pre-determined
Flue gas adjustment: with manually adjustable valve

Standard flue outlet position: top

•Fuel: wood

The MA 263 SL by Piazzetta is the One-piece Firebox with Vertically-sliding Door and Natural Convection for Wood Fireboxes that will ensure you low consumption, high efficiency and easy installation. Find out further information

## **TECHNICAL DETAILS**

•Energy efficiency class A+

•Rated output max kW 12,5

•Rated efficiency power % 86,7

•Rated consumption max kg/h 3,6

Vertically sliding opening cm 30

•Firebox opening (W) - Dimensions for the passage of wood

•Firebox opening (H) - Dimensions for the passage of wood cm 22,5

•Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 90,5

•Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 45

•Weight kg 260 •Model MA 263 SL PLUS

