## MA 283 D/S SL PLUS

**GENERAL FEATURES** 

\*Heating: natural convection, radiation or optional ductable forced ventilation with the Multifuoco System® or Multifuoco System Plus,

Structure: coated steel with closed firebox

•Firebox: Aluker®

Hearth: cast ironHood: steel

•Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. Openable with vertically-sliding system and door for cleaning

·Door profile: coated steel

·Handle: coated steel

Primary air: manually adjustable

·Secondary air: pre-determined

•Flue gas adjustment: with manually adjustable valve

•Standard flue outlet position: top

·Fuel: wood

The MA 283 D/S SL by Piazzetta is the One-piece Firebox with Vertically-sliding Door and Natural Convection for Wood Fireboxes that will ensure you low consumption, high efficiency and easy installation. Find out further information

## **TECHNICAL DETAILS**

•Energy efficiency class A

•Rated output max kW 16,0

•Rated efficiency power % 80,4

•Rated consumption max kg/h 4,8

Vertically sliding opening cm 35

\*Firebox opening (W) - Dimensions for the passage of wood cm 78,5

\*Firebox opening (H) - Dimensions for the passage of wood cm 27,5

\*Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 90

•Mouth of firebox (D) - Minimum dimensions of mouth of cladding cm 51

\*Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 51,5  $\,$ 

•Model MA 283 D SL PLUS

