

The MA 283 D/S SL by Piazzetta is the One-piece Firebox with Vertically-sliding Door and Natural Convection for Wood Fireboxes that will ensure you low consumption, high efficiency and easy installation. Find out further information

MA 283 D/S SL PLUS

GENERAL FEATURES

- Heating: natural convection, radiation or optional ductable forced ventilation with the Multifuoco System® or Multifuoco System Plus,
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: cast iron
- Hood: steel
- Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. Openable with vertically-sliding system and door for cleaning
- Door profile: coated steel
- Handle: coated steel
- Primary air: manually adjustable
- Secondary air: pre-determined
- Flue gas adjustment: with manually adjustable valve
- Standard flue outlet position: top
- Fuel: wood

TECHNICAL DETAILS

- Energy efficiency class A
- Rated output max kW 16,0
- Rated efficiency power % 80,4
- Rated consumption max kg/h 4,8
- Vertically sliding opening cm 35
- Firebox opening (W) - Dimensions for the passage of wood cm 78,5
- Firebox opening (H) - Dimensions for the passage of wood cm 27,5
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 90
- Mouth of firebox (D) - Minimum dimensions of mouth of cladding cm 51
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 51,5
- Weight kg 270
- Weight kg 270
- Model MA 283 S SL PLUS