

MA 261 SL

Wood firebox that blends clean design lines with ease of use. Its perfect construction linearity offers a wide variety of installation options. The screen-printed glass frames the fire and makes it the distinctive feature of the home.



GENERAL FEATURES

- Heating: natural convection and radiation
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: cast iron
- Hood: steel
- Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. Openable with vertically-sliding system and door for cleaning
- Door profile: coated steel
- Handle: coated steel
- Primary air: manually adjustable
- Secondary air: pre-determined
- Flue gas adjustment: with manually adjustable valve
- Standard flue outlet position: top
- Fuel: wood

TECHNICAL DETAILS

- Energy efficiency class A+
- Rated output max kW 16
- Rated efficiency power % 81,5
- Rated consumption max kg/h 4,8
- Vertically sliding opening cm 37,5
- Firebox opening (W) - Dimensions for the passage of wood cm 76,0
- Firebox opening (H) - Dimensions for the passage of wood cm 30
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 79,5
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 55,5
- Weight kg 206
- Model MA 261 SL

