

Wood firebox that blends clean design lines with ease of use. Its perfect construction linearity offers a wide variety of installation options. The screen-printed glass frames the fire and makes it the distinctive feature of the home.

# MA 283 D/S SL



## GENERAL FEATURES

- Heating: natural convection and radiation
- Structure: coated steel with closed firebox
- Firebox: Aluker®
- Hearth: cast iron
- Hood: steel
- Opening: door in coated steel with self-cleaning ceramic glass resistant to 750°C. Openable with vertically-sliding system and door for cleaning
- Door profile: coated steel
- Handle: coated steel
- Primary air: manually adjustable
- Secondary air: pre-determined
- Flue gas adjustment: with manually adjustable valve
- Standard flue outlet position: top
- Fuel: wood

## TECHNICAL DETAILS

- Energy efficiency class A
- Rated output max kW 13,5
- Rated efficiency power % 75
- Rated consumption max kg/h 4.1
- Vertically sliding opening cm 35
- Firebox opening (W) - Dimensions for the passage of wood cm 78,5
- Firebox opening (H) - Dimensions for the passage of wood cm 27,5
- Mouth of firebox (W) - Minimum dimensions of mouth of cladding cm 90
- Mouth of firebox (D) - Minimum dimensions of mouth of cladding cm 51
- Mouth of firebox (H) - Minimum dimensions of mouth of cladding cm 51,5
- Weight kg 185
- Model MA 283 DX SL

