## **P189 TH ACS**

Thermo Pellet stove, cladded in Majolica in the following colours: Bianco Grigio, Bordeaux, Nero Opaco, Grigio Cerato, Rosso Lava and Terra Oriente. Rolling top system for easy loading. An original solution which stands out discreetly, becoming a valid choice for heating the domestic heating circuit.



## **GENERAL FEATURES**

- ·Heating: hot water production forced ventilation
- ·Cladding: coated steel •Top: steel - majolica
- ·One-piece firebox: steel
- ·Boiler: steel
- •Firebox: steel Aluker®
- •Fume deflector: steel
- ·Ash conveyor: steel
- •Exchanger cleaning: rotor cleaning system, Patented
- Brazier: steel
- ·Expansion tank: as standard feature
- ·Standard circulator pump: high efficiency
- ·Safety valve and relief valve: as standard feature •Door: cast iron with ceramic glass resistant to 750°C
- ·Handle: steel with nickel-plated finish
- Optional flue outlet: LH side
- •Standard flue outlet position: LH rear
- •Function control: panel with display and digital controls
- •Power adjustment: automatic with 16 levels depending on the set temperature
- •Timer-controlled thermostat with programming: 6 daily time frames
- Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Energy Saving: yes
- •Eco Function: yes
- Frost Function: yes
- ·Probe for managing storage tank: as standard feature
- •Probe for managing DHW storage tank: as standard feature
- •Can be connected to an external thermostat: yes
- ·AUX control: yes
- ·Ash vacuum cleaner: as standard feature
- •Flue gas chamber ash pan: removable
  •Ventilation: optional
- •Electronically-controlled anti-condensation valve: as standard feature
- ·Installation: wall corner
- •Flush with the wall installation: yes
- Combustion air kit: optional

## **TECHNICAL DETAILS**

- Energy efficiency class A+
- •Rated thermal power (min max) kW 7,6 25,7 •Efficiency (min max) % 95,7 95,0

- \*Elliciticity (min max) % 95,7 95,0

  \*Max operating pressure bar 1.5

  \*3-bar safety discharge valve Ø 1/2"

  \*Heat system delivery Ø 3/4"

  \*Heat system repution (min max) ka/l'

  \*Potod consumption (min max) ka/l
- •Rated consumption (min max) kg/h 1,6 5,6
- ·Weight kg 275
- •Standard flue outlet Ø cm 10
- •Model P189 TH ACS

## **COVERS**









