P188 TH

Thermo Pellet stove that can also release hot air into the room. Coated steel cladding and top surface in Majolica. Available in the following colours: Bianco, Bordeaux, Brunito and Grigio. Equipped with a practical shell and tube cleaning system which has rotating elements to keep it working efficiently.



GENERAL FEATURES

- ·Heating: hot water production forced ventilation
- ·Cladding: coated steel
- ·Top: majolica and steel
- ·One-piece firebox: steel
- ·Boiler: steel
- •Firebox: steel Aluker® •Fume deflector: steel
- ·Ash conveyor: steel
- •Exchanger cleaning: rotor cleaning system, Patented
- Brazier: steel
- ·Expansion tank: as standard feature
- ·Standard circulator pump: high efficiency
- ·Safety valve and relief valve: as standard feature
- •Door: cast iron with ceramic glass resistant to 750°C
- ·Handle: steel with nickel-plated finish
- Optional flue outlet: LH side
- •Standard flue outlet position: LH rear
- •Function control: panel with display and digital controls
- •Power adjustment: automatic with 16 levels depending on the set temperature
- •Timer-controlled thermostat with programming: 6 daily time frames
- Glass cleaning: continuous air flow
- Cyclic brazier cleaning: yes
- Energy Saving: yes
- •Eco Function: yes
- Frost Function: yes
- ·Probe for managing storage tank: as standard feature
- •Probe for managing DHW storage tank: as standard feature
- •Can be connected to an external thermostat: yes
- ·AUX control: yes
- *Ash vacuum cleaner: as standard feature
 *Flue gas chamber ash pan: removable
 *Ventilation: optional

- ·Electronically-controlled anti-condensation valve: optional
- ·Installation: flush with the wall / corner
- •Flush with the wall installation: yes
- . Combustion air kit: optional

TECHNICAL DETAILS

- Energy efficiency class A+
- •Rated thermal power (min max) kW 7,4 19,6 •Efficiency (min max) % 94,4 93,0

- *Efficiency (min max) % 94,4 93,0

 *Max operating pressure bar 1.5

 *3-bar safety discharge valve Ø 1/2"

 *Heat system delivery Ø 3/4"

 *Heat system repetitor (min max) ka/l'

 *Potent operation (min max) ka/l' •Rated consumption (min - max) kg/h 1,6 - 4,3
- Weight kg 210
- •Standard flue outlet Ø cm 10
- ·Model P188 TH

COVERS







